

## VILLAGE OF LYNDONVILLE

### BIDS FOR SIDEWALK CONSTRUCTION SPECIFICATIONS

#### A. EXISTING SIDEWALK REMOVAL

1. The contractor will remove existing sidewalk, related debris, and rough excavate to approximate subbase.
2. Removal will be in lengths in which the contractor intends to form and pour in a reasonable time.

#### B. SIDEWALK CONSTRUCTION

1. The contractor is responsible for installing subbase with compacted #1 crushed limestone crusher run to a minimum depth of 4 inches.
  - a. The Village will supply stone for contractor to prepare subbase.
2. All new or replacement sidewalks shall be of concrete having a minimum thickness of 4 inches of concrete except, sidewalks across driveways which shall be a minimum of 6 inches thick.
  - a. The concrete mixture must be a minimum strength of three thousand five hundred (3500) pounds per square inch (equal to a six bag mix) with #1 stone. A strength of four thousand (4000) pounds per square inch (equal to a six and one-half bag mix) with #2 stone is recommended.
  - b. Wire mesh shall be used according to good, standard sidewalk construction practices, or in place of wire mesh fiber reinforced concrete may be used.
3. All concrete sidewalk blocks must have a minimum width of 48 inches and replacement sidewalk sections length shall conform to the lengths already established in the immediate area.
4. An expansion joint is required every 20 feet at a minimum, and also at the end of any adjoining sidewalks, and must meet grade of adjoining sidewalks.
5. Sidewalk must be laid out and formed to a grade which does not allow for water to puddle or pond on final sidewalk grade.
6. A broom finish is required on the concrete and a cure/hardener spray is to be applied by the contractor. The contractor is responsible for any vandalism or defacing that might occur before concrete has hardened.

C. **FINAL GRADE:**

The contractor will place topsoil and grass seed at lawn areas and fill in driveways with similar existing material, tapered to existing original grade to the Village's satisfaction.

D. **SAFETY DEVICES:**

1. Any safety device such as (reflective barrels, cones, signs or ribbon) that is needed to warn others of a hazardous condition must be supplied and used by the contractor.

E. **PERMIT AND INSURANCE:**

1. Any permit required by NYSDOT and or any other agency is the contractor's responsibility, and proof of insurance is required prior to the start of the project.

F. **INSPECTION:**

1. All work must be done in accordance with these specifications.
2. The Village of Lyndonville Superintendent of Public Works or the Village Board will from time to time inspect the project and may require the contractor to remove and replace any construction that does not meet the specifications or does not have acceptable quality.

**VILLAGE OF LYNDONVILLE**  
**SIDEWALK BID SHEET**

Name of Company \_\_\_\_\_ DATE: \_\_\_\_\_

Name and Title of Officer \_\_\_\_\_

Signature of Officer \_\_\_\_\_

Telephone Number \_\_\_\_\_

**BID**

4 inch \$ \_\_\_\_\_ per square foot

6 inch \$ \_\_\_\_\_ per square foot

Contractors must submit proof of Worker's Compensation, Disability and Liability insurance, as well as copies of the certified payroll, paying employee's at current prevailing wage for the project.

The Village of Lyndonville has the right to accept or reject any or all bids.

**Please return to the Village Clerk by noon on July 31, 2023**

**Fax:** 585-765-2394

**Email:** villageoflyndonville@rochester.twcbc.com

**Mailing Address:** 2 South Main Street, Lyndonville, NY 14098